



## Bio Oil

- Description:** Bio Oil is a deeply penetrative, lightly pigmented enriching oil for decking and furniture.
- Suitable Surfaces:** Deep penetrating Bio Oil is formulated for use on all timbers and is ideal for hardwoods that tend to surface check (split), it is also suitable for bamboo.
- Special Feature:** Bio Oil is simple to recoat.  
Nourish the timber when necessary using a lambswool applicator or brush. Frequent light coats will keep your deck or outdoor furniture in pristine condition.
- How to Apply:** Bio Oil can be applied by brush or lambswool applicator.  
Use Sap Strip on all timbers under 12 months old to remove extractives and tannins which can slow the drying and curing time. Dirty or grey weathered wood should be cleaned with Dex Prep and let dry prior to treating.  
  
For pre oiled timber in poor condition use Power Clean followed by Dex Prep. After cleaning apply 1 coat of Bio Oil allowing it to soak as much as possible into cracks and the grain.
- Drying time** Drying time on 1<sup>st</sup> coat 24-36 hours depending on porosity of timber. Subsequent coats will dry faster.
- Coverage:** 8-10sq metres per litre. This will depend on the porosity of the timber. A minimum of 2 coats is necessary.
- Recoating:** Bio Oil can be recoated easily when necessary, give the surface a wash down with soapy water if the coating is stable and reapply. If the timber is exposed prepare with Dex Prep to clean the timber before applying.
- Clean Up** Wash brushes and tools in soap and water.