



## Quantec

- Description:** Quantec is a deeply penetrative, low odour water repellent treatment that offers broad spectrum treatment and protection against degradation caused by mould, mildew and algae. It is a water dispersed oil coating that is a non hazardous substance by work safe criteria.  
Quantec is excellent in helping to prevent moisture attack, cupping, splitting and warping by deeply penetrating into the timber and binding the wood fibres together.
- Suitable Surfaces:** Quantec is suitable on all cleaned softwood and hardwood timbers that have not been previously painted.
- Special Feature:** Quantec has new protective technology in the form of a Time Release Fungicide which stops leaching of fungicide from the coating during the weathering process.
- How to Apply:** Quantec can be applied by brush, roller or spray and can be supplied as a dip coating. Use Sap Strip on all timbers under 12 months old to remove extractives and tannins which can slow the drying and curing time. Dirty wood should be cleaned with Dex Prep and let dry prior to treating.  
Flood coat with 1 coat of Quantec, soaking as much as possible into cracks and the grain.  
For wood that will not have a finish (painted or stained) apply 2 coats.  
Drying time on 1<sup>st</sup> coat 24-48 hours depending on porosity of timber.  
Subsequent coats will dry faster.
- Coverage:** 4-6sq metres per litre.
- Recoating:** Quantec if not maintained every 6-9 months will grey off but the properties will remain in the timber.
- Overcoating:** Quantec can be over coated with all Quantum products or Acrylic coatings.